

SCAN COMBIFLEX 650/650 DSP



The Scan Combiflex 650 and Scan Combiflex 650 DSP is two robust and stable machines made of steel, designed for both residential and commercial applications with its 650 mm / 25.6" grinding width.

The Scan Combiflex 650 features industrial grade components and is designed for durability and simple maintenance. This model can also be used for wet grinding with the included water connection valve (pressurized water hose required).

Scan Combiflex 650 DSP is the optimal grinding machine when grinding. By the guiding system on the panel the machine operator gets, via the sensors, feedback and warnings when the tool wear is too high or is completely worn out. The sensors continuously measure the wear and thickness of the tools to guide the operator to optimal consumption. Savings of up to 25% has been demonstrated when changing to the model DSP.

Scan Combiflex 650 and Scan Combiflex 650 DSP is equipped with our patented drive system to power the three grinding heads. The drive system is constructed with high quality components like a double-sided toothed belt in combination with a ring gear. The components are carefully selected to ensure high reliability and high quality.

STABLE GRINDING MACHINES MADE OF STEEL



**GRINDING DISC
PLANETARY**



GRINDING WIDTH
650 mm / 25,6"



WEIGHT
320 kg / 705 lbs

TECHNICAL DATA

SCAN COMBIFLEX 650

	Standard	1-fas
Voltage:	400 V 3~	230 V 1~
Motor power:	7,5 kW / 10 hp	4 kW / 5 hp
Current:	16 Amp.	30 Amp.
Frequency:	50-60 Hz	50-60 Hz
Grinding speed:	350-1100 rpm	350-900 rpm
Grinding disc:	3 x 220 mm / 3 x 8,5"	3 x 220 mm / 3 x 8,5"
Grinding width:	650 mm / 25,6"	650 mm / 25,6"
Weight:	320 kg / 705 lbs	320 kg / 705 lbs
Grinding pressure:	180 kg / 396 lbs	180 kg / 396 lbs
Other:	CE-marking	CE-marking

SCAN COMBIFLEX 650 DSP

	Standard	1-fas
Voltage:	400 V 3~	230 V 1
Motor power:	7,5 kW / 10 hp	4 kW / 5 hp
Current:	16 Amp.	16 Amp / 30 Amp
Frequency:	50-60 Hz	50-60 Hz
Grinding speed:	350-1100 rpm	350-900 rpm
Grinding disc:	3 x 220 mm / 3 x 8,5"	3 x 220 mm / 3 x 8,5"
Grinding width:	650 mm / 25,6"	650 mm / 25,6"
Weight:	320 kg / 705 lbs	320 kg / 705 lbs
Other:	CE-marking	CE-marking



Weight package
available 18 kg / 39 lbs.



Scan Combiflex 650 DSP is
equipped with a display on
the instrument panel.



Recommended vacuum:
Scanmaskin 7000 WS,
Scanmaskin 9000 WS



Equipped with our patent-
ed planetary system
with three head drums.

SCANMASKIN
MACHINES-MINERALS-KNOW-HOW

www.scanmaskin.com