

## FEROX 320 WORLD SERIES



Ferox 320 World Series is a very powerful machine for both milling and shaving. Depending on the choice of tools, you can adapt the areas of use, from removing of concrete asphalt, coatings to road markings. The different tool options are designed to remove the hardest applications, coatings and floors. By using the 300 mm variable diamond drum blades, it allows for cutting depth of 2mm in a single pass. Use "cutter drum" or "milling drum" for effective scarifying.

The motor on the Ferox 320 is positioned directly above cutting drum, for maximum head pressure. The machine has an ergonomic design, with vibration dampening handle bar and control panel for operators' comfort and safety.

The machine features frame protection, as well as robust maintenance free bearings, ensuring extended service life. For a dust free operation, you can connect a dust collector to the 70 mm dust port. The machine has an optional water injection system to reduce airborne dust when not using a dust collector.

### ROBUST AND POWERFUL SCARIFIER/SHAVER



**TOOL RPM**  
1649/1644 rpm



**WORKING WIDTH**  
320 mm/12"




**WEIGHT**  
300 kg /661 lbs


# TECHNICAL DATA

## FEROX 320 WS


Working width:	320 mm / 12"	Weight:	300 kg / 661 lbs
Voltage:	400 V	Height:	118 cm / 46"
Frequency:	50 Hz	Length:	98 cm / 38"
Phase:	3	Width:	63 cm / 25"
Current:	20,6-32,6 amp	Tool rpm:	1649/1644 rpm
Motor power:	11-18,5 kW	Dust port diameter:	70/120 mm/ 2,7"/ 4,7"
Motor rotation speed:	2880 rpm		




The motor is placed above cutting drum, for maximum head pressure



Height adjustment with hand wheel and quick lift.



Equipped with a wheel drive, for self-propelled machine



Comprehensive range of cutters.

**SCANMASKIN**  
MACHINES-MINERALS-KNOW-HOW

Phone: +1 425 209 0147  
Email: info@scanmaskin.com  
Website: www.scanmaskin.com