

SALES START SPRING 2025!

SCANMASKIN

MACHINES-MINERALS-KNOW-HOW



SCANMASKIN 750

Robust Floor Grinder for Demanding Projects

The Scanmaskin 750 is a powerful, extremely robust, and stable grinder, constructed entirely from durable steel. Equipped with reinforced bearings, shafts, and drive belts, the grinder is designed to deliver high operational reliability over time. With a grinding width of 750 mm / 29.5", the Scanmaskin 750 is suitable for both residential projects and larger commercial applications. The Scanmaskin 750 is the optimal choice for polishing, grinding, and removing even the thickest coatings.

Durable and User-Friendly Design

The grinder is built to be extremely durable and easy to maintain. It is also designed to minimize vibrations and operator strain, enhancing the working environment. With the option for wet grinding, enabled by a convenient water hose connection, the machine's flexibility is further increased.

Ergonomic and Extra-Durable Grinding Heads

The Scanmaskin 750 is equipped with three grinding heads, each with a diameter of 280 mm / 11", cast in one solid piece of ductile iron. This design minimizes vibrations and provides a more ergonomic working environment. To ensure long service life and extra durability, the plates are laser-hardened.

Easy Transport and Smooth Handling

The grinder's handle can be easily folded back, making transport and storage hassle-free. In tight spaces, the handle can remain folded, and the built-in handles make the grinding machine easy to maneuver.

Patented Drive System for Reliable Performance

The Scanmaskin 750 features our patented drive system powering the three grinding heads. The system is designed with a double-sided timing belt and a gear ring. Each part is carefully selected to ensure maximum reliability and top performance in all types of projects.



POWERFUL, EXTREMELY ROBUST AND STABLE GRINDER



GRINDING DISC
PLANETARY



GRINDING WIDTH
750 mm / 29,5"




WEIGHT
372 kg / 820 lbs

TECHNICAL DATA

Art.No.:	575000
Voltage:	3~ 230 Dual Phase / 400-480 V
Motor power:	9.5 kW / 13 hp
Current:	32 Amp
Frequency:	50-60 Hz
Grinding head speed:	250-1150 rpm

Grinding head:	3 x 280 mm / 3 x 11"
Grinding width:	750 mm / 29,5"
Weight:	372 kg / 820 lbs
Grinding pressure:	280 kg / 620 lbs
Other:	CE-marking



The handle can be easily folded backward.




3 grinding heads, 280 mm / 11" in diameter, cast in one piece of ductile iron and laser-hardened.



Powerful, robust, and stable floor grinder!



Our patented drive system ensures maximum and reliable operational performance.



Grinding width 750 mm / 29,5"



Recommended dust extractors:
Scanmaskin 7000 WS
Scanmaskin 9000 WS

SCANMASKIN
MACHINES-MINERALS-KNOW-HOW

www.scanmaskin.com