★★★
PREMIUM

Shot blaster FBE225

Working width 225 mm

7.5 kW turbine power on 225 mm working width

Perfect blast patterns with 5-bladed blastwheel

FBE225 maintenance and tool box

The FBE225 shot blaster combines high productivity with low overall height and weight. Its modular design opens up unique application possibilities. The shot blasting width can be increased to up to 455 mm by adding the FBE225 expansion module. The modular combinations can in turn be disassembled into their basic FBE225 components and be transported to locations previously inaccessible to conventional shot blasters of the same blasting power. The drive unit enables an even and infinitely adjustable feed. Maintenance work on the FBE225 after the first 300 operating hours can be carried out easily on site without special tools and with little loss of time.

TYROLIT

System & Accessories

Technical data

Shot blaster	**FBE225**
Type no.	11002930
Reference model Contec	MODUL 200 XL
Voltage / Frequency	400 V / 50 Hz
Working width	225 mm
Nominal power	7.5 kW (0.17 kW)
Nominal current	13.6 A
Speed (drive motor)	2 880 rpm (3 000 rpm)
Application	Dry
Hose connection	Camlock 3" male
Recommended vacuum cleaner	VCE3000C, VCE5522C, VCE7522C

Design	
Variable drive unit for forward and backward motion	•
LED headlights	•
Operating hours counter	•
Foldable rear axle for transport	•

Dimensions & weight	
Length	1 480 mm
Width	340 mm
Height	1 050 mm
Weight	210 kg

Accessories

11004019	Service box incl. tools and wear parts FBE225
11004051	FBE225 extension unit 400 V 16 A 7.5 kW 210 kg
11004035	Magnetic brush 50 cm
11002991	Magnetic brush 70 cm
11004017	Extraction hose Ø 70 mm, 15 m
11004015	Blast wheel set FBE200/225 + cage
11003402	Side lining blast chamber FBE200/225
11004007	Top lining blast chamber FBE200/225
11004682	Steel shot S 390 F20 VE 25 kg
11018779	Magnetic work LED